



WS-1210T

电子计算器 /
Electronic Calculator



E-IM-3222

使用说明书 **中文**
Instruction **EN**

运算例子 / Calculation Examples

计算举例/ Calculation	按键操作 / Operation	显示/ Display
$2 \times 2 - 3 = 6$ $-7 \times 9 \div 9 = -63$	$2 \times 2 = 6$ $7 \times 9 \div 9 = 63$ =	(0.) (6.00) (-63.00)
▼ 附加模式运算/Add Mode \$14.90+\$0.35 = 15.25	1490 \oplus 35 =	(15.25)
▼ 浮动运算/Floating Calculation 8÷3×9 =23.9999999999	8 \div 3 \times 9 =	(23.9999999999)
▼ 向上圆正/Round-up 28÷3 =9.3333333333	28 \div 3 =	(9.34)
▼ 向下圆正/Round-down 11÷3 =3.6666666666	11 \div 3 =	(3.66)
▼ 相反/Reverse 10÷5=2 $\swarrow \searrow$ 5÷10=0.5	10 \div 5 (RV) =	(0.50)
▼ 百分比运算/Percentage 1200+(1200×20%)=1,440 1200-(1200×20%)=960	1200 \oplus 20 % 1200 \ominus 20 %	(1'440.00) (960.00)

计算举例/ Calculation	按键操作 / Operation	显示/ Display
▼ 税项运算/Tax calculation 设定税率/Set tax rate 税率/Rate:5% 5 RATE SET (TAX% 5.) 税率增加/Add tax amount \$2,000成本不包税率/Cost \$2,000 without tax 销售价格包税率/Selling price with tax =?(\$2,100) 税率/Tax=?(\$100) 税率减少/Deduct the tax amount 销售价格\$3,150包税率/Selling price \$3,150 with tax 成本价格不包税率/Cost without tax=?(\$3,000) 税率/Tax=?(\$150)	5 RATE SET 2000 TAX+ 3150 TAX-	(2'100.00) (100.00) (3'000.00) (150.00)
▼ 记忆运算/Memory 3×4= 12 -) 6÷0.2= 30 -18 +) 200 182	$3 \times 4 = 12$ $6 \div 0.2 = 30$ -18 200 182	(0.) (M 12.00) (M 30.00) (M -18.) (M 200.00) (M 182.)
▼ 总计运算/Grand Total 4×30=120 +) 5×60=300 420 +) 23×35= 805 1,225	$4 \times 30 = 120$ $5 \times 60 = 300$ 420 $23 \times 35 = 805$ 1,225	(0.) (GT 120.00) (GT 300.00) (GT 420.) (GT 805.00) (GT 1'225.) (GT 1'225.)
▼ 销售价运算/Mark-up 成本/Cost\$2,000 利润20%/Profit 20% of selling price 销售价格/Selling price=?(\$2,500) 利润/Profit=?(\$500)	2000 \div 20 MU MU	(2'500.00) (500.00)
▼ 成本价运算/Mark-down 销售价格/Selling price\$2,400 利润20%/Profit 20% of cost 成本/Cost=?(\$2,000) 利润/Profit=?(\$400)	2400 \div 20 MU MU	(2'000.00) (400.00)
▼ 溢出运算/Overflow 1) 123456789 x 78900= 9.740740652100 (溢出/ERROR)→ 2) 6÷0= 0 (溢出/ERROR)	$123456789 \times 78900 =$ $6 \div 0 = 0$	(E 9.74074065210) (9.74074065210) (E 0.) (0.)


- 使用本产品前，请务必阅读本使用说明书；保留备用；理解本说明书内容后，请正确使用。

⚠ 注意事项


- 1) 切勿在阳光直射下使用计算器。亦应避免把计算器放置于阳光猛烈、潮湿、肮脏(如灰尘)及温度急速变化的地方。
- 2) 使用柔软的干布拭净计算器的外部。切勿使用清水或清洁溶剂。
- 3) 切勿使用坚硬物体或其它尖锐物体按压计算器的按键，避免在机上留下刮痕。
- 4) 切勿扭曲或弯曲或尝试拆开计算器。
- 5) 电力不足可能会使存储器内容损坏或出现故障，请重新开启计算器。

供电电源

本计算器配有两种电源：太阳能及碱性电池。碱性电池的使用时间完全取决于个别的使用情况。

- ⓘ 电磁干扰或静电释放可引起显示故障或存储器的内容丢失或被改变。若出现此情况，请按  键重新开始计算。

数据溢出功能

在下列情况下，显示幕上将显示出"E" (错误) 字样，键盘也会被锁定，不能继续操作。按  键可清除溢出。可导致溢出的情况如下：

- 1) 计算结果或内存数字超过12位数字。
- 2) 进行除以"0"的计算。

规格

电源：太阳能及碱性电池 (LR44x1)
 工作温度范围：摄氏0至40度
 自动断电：约7分钟
 体积：198(长) x 150(宽) x 38(高) 毫米
 重量：238克
 产品标准：GB/T4967-1995
 本使用说明书的规格及内容如有改动，恕不另行通知

佳能电产香港有限公司

香港新界葵涌货柜码头路82-100号
 永得利广场第1期17楼

北京通泰嘉怡科技有限责任公司

北京市西城区北展北街华远企业中心D座
 1单元505室


- Before using this product, please read this manual carefully. And keep it on hand for future reference.

⚠ CAUTION


- 1) Avoid using, placing or storing the calculator in places subject to strong sunlight, rapid temperature change, humid or dusty areas.
- 2) Use a dry cloth to clean the casing of the unit. Do not use water, organic solvents or detergents.
- 3) Avoid using the calculator in places where there are iron filings, as this may affect the electrical circuits of the calculator.
- 4) Do not twist or bend or attempt to open the calculator.
- 5) Lack of electricity may cause damage or failure of memory content, please reset the sample.

POWER SUPPLY

This calculator has two power sources: battery and solar. The duration of the battery depends on individual usage.

- ⓘ Electromagnetic interference or electrostatic discharge may cause the display to malfunction or the contents of the memory to be lost or altered. Should this occur, press the  key and re-start your calculation from the beginning.

OVERFLOW FUNCTIONS

In the following cases, error message (E) will be shown on the display. The keyboard is electronically locked, and further operation is impossible. Press  to clear the overflow. The overflow occurs when:

- 1) The result or the memory content exceeds 12 digits to the left of the decimal point.
- 2) Dividing by "0".

SPECIFICATIONS

Power Source:

Solar cell and alkaline battery (LR44 x 1)
 Operating Temperature : 0°C to 40°C
 Automatic Power-off : approx. 7 minutes
 Dimension: 198(L) x 150(W) x 38(H) mm
 Weight : 238g
 All specifications and contents of this instruction are subject to change without notice