

中文及英文使用说明书及重要备注印刷在盒内/  
Instruction Manual and Important Notes are printed inside

E-IM-2735

运算例子 / Calculation Examples

运算 / CALCULATION	操作 / OPERATION	显示 / DISPLAY
<b>混合运算 / MIXED</b> $2 \times 2 = 6$ $-7 \times 9 = -63$ $(2+4) \div 3 \times 8.1 = 16.2$	$2 \times 2 = 6$ $7 \times 9 = 63$ $2 + 4 = 6$ $6 \times 8.1 = 48.6$ $48.6 \div 3 = 16.2$	( 0.) ( 6.) ( -63.) ( 16.2)
<b>分数 / POWER, FRACTION</b> $3^3 = 27$ $1/2 = 0.5$	$3 \times 3 = 27$ $1 \div 2 = 0.5$	( 27.) ( 0.5)
<b>反向 / REVERSE</b> $10 \div 5 = 2$ $5 \div 10 = 0.5$	$10 \div 5 = 2$ $5 \div 10 = 0.5$	( 0.5)
<b>增加/减少运算 / MARK-UP/DOWN</b> <b>Mark up:</b> Cost = \$2,000 Profit = 20% of selling price Selling price = ? (\$2,500) Profit = ? (\$500)  <b>Mark down:</b> Selling price = \$2,400 Profit = 20% of cost Cost = ? (\$2,000) Profit = ? (\$400)	$2000 \div 20 = 100$ $2000 + 100 = 2100$ $2100 \times 20 = 420$ $2100 + 420 = 2520$ $2520 - 20 = 2500$ $2500 - 200 = 2300$ $2300 \times 20 = 460$ $2300 - 460 = 1840$	( 2'500.) ( 500.) ( 2'000.) ( 400.)
<b>总和运算 / GRAND TOTAL</b> $30 \times 40 = 1,200$ $50 \times 60 = 3,000$ $4,200$ $235 \times 35 = 8,225$ $12,425$	$30 \times 40 = 1200$ $50 \times 60 = 3000$ $235 \times 35 = 8225$ $12425$	( 0.) (GT 1'200.) (GT 3'000.) (GT 4'200.) (GT 8'225.) (GT 12'425.) ( 12'425.)
<b>记忆运算 / MEMORY</b> $3 \times 4 = 12$ $6 \div 0.2 = 30$ $-18$ $200$ $182$	$3 \times 4 = 12$ $6 \div 0.2 = 30$ $200 - 18 = 182$	( 0.) (M 12.) (M 30.) (M -18.) (M 200.) (M 182.) ( 182.)
<b>溢出 / OVERFLOW</b> $123456789 \times 78900 =$ $9740740652100$ (溢出/ERROR)  $6 \div 0 = 0$ (溢出/ERROR)	$123456789 \times 78900 =$ $9740740652100$ $6 \div 0 = 0$	(E 9.74074065210) ( 9.74074065210) (E 0.) ( 0.)

AS-120

■ 在使用本产品前，请务必先仔细阅读本使用说明书。

中国语

电源

本计算器配有两种电源，太阳能及碱性电池。电池的使用时间完全取决于个别的使用情况。  
(注：不要试图自行更换电池，请到佳能维修服务中心，专业人员为您更换电池。)

■ 电磁干扰或静电放电可引起显示故障或内存中的内容丢失或改变。若出现此情况，请按  $\text{ON/CA}$  键重新开始计算。

规格

电 源：太阳能电池及碱性电池 (LR44 x 1)

自动断电：约7分钟

操作温度：0 至 40度(华氏 32 至 104度)

体 积：145毫米(长) x 100毫米(宽) x 33.5毫米(高)

重 量：108 克

(规格如有改动恕不另行通知)

中国印制 /  
Printed in China

■ Before using this product, please read this manual carefully.

ENGLISH

POWER SUPPLY

This calculator comes with a dual power source, solar cell and alkaline battery. The battery life will depend on individual usage.

(Note: Do not attempt to change the battery by yourself. Have a Canon Service Center change the battery for you).

■ Electromagnetic interference or electrostatic discharge may cause the display to malfunction or the contents of the memory to be lost or altered. Should this occur, press the  $\text{ON/CA}$  key and re-start your calculation from the beginning.

SPECIFICATION

Power Source : Solar Cell and Alkaline battery (LR44 X 1)

Automatic power-off function: Approx. 7 minutes

Usable Temperature : 0°C to 40°C (32°F to 104°F)

Dimensions : 145mm (L) x 100mm (W) x 33.5mm (H) /

5-23/32" (L) x 3-15/16" (W) x 1-21/64" (H)

Weight : 108g (3.65oz)

(Subject to change without notice)

备注/NOTE：部分机身采用佳能循环再生物料制成 / Some parts are made from recycled Canon product materials

修订日期: 2012.02

© CANON ELECTRONIC BUSINESS MACHINES (H.K.) CO., LTD. 2012

佳能电产香港有限公司

香港新界葵涌货柜码头路82-100号永得利广场第1期17楼

北京博怡嘉业科技股份有限公司

北京市西城区北展北街华远企业中心D座1单元505室