

中文及英文使用说明书及重要备注印刷在盒内/
Instruction Manual and Important Notes are printed inside

E-IM-2736

运算例子 / Calculation Examples

运算 / CALCULATION	操作 / OPERATION	显示 / DISPLAY
		1'234'567'890.12
混合运算 / MIXED $2 \times 2 \ominus = 6$ $-7 \times 9 = -63$ $(2+4) \div 3 \times 8.1 = 16.2$	$2 \times 2 \ominus = 6$ $-7 \times 9 = -63$ $(2+4) \div 3 \times 8.1 = 16.2$	(0.) (6.00) (-63.00) (16.20)
常数运算 / CONSTANT $2+3=5$ $4+3=7$ $1-2=-1$ $2-2=0$ $5 \times 3=15$ $5 \times 4=20$ $6 \div 3=2$ $9 \div 3=3$	$2+3=5$ $4+3=7$ $1-2=-1$ $2-2=0$ $5 \times 3=15$ $5 \times 4=20$ $6 \div 3=2$ $9 \div 3=3$	(5.00) (7.00) (-1.00) (0.00) (15.00) (20.00) (2.00) (3.00)
份数 / POWER, FRACTION $3^3 = 27$ $1/2 = 0.5$	$3^3 = 27$ $1/2 = 0.5$	(27.00) (0.50)
反向 / REVERSE $10 \div 5 = 2$ $5 \div 10 = 0.5$	$10 \div 5 = 2$ $5 \div 10 = 0.5$	(0.50)
总和运算 / GRAND TOTAL $30 \times 40 = 1,200$ $50 \times 60 = 3,000$ $4,200$ $235 \times 35 = 8,225$ $12,425$	$30 \times 40 = 1,200$ $50 \times 60 = 3,000$ $4,200$ $235 \times 35 = 8,225$ $12,425$	(0.) (GT 1'200.00) (GT 3'000.00) (GT 4'200.) (GT 8'225.00) (GT 12'425.) (GT 12'425.)
记忆运算 / MEMORY $3 \times 4 = 12$ $6 \div 0.2 = 30$ -18 200 182	$3 \times 4 = 12$ $6 \div 0.2 = 30$ -18 200 182	(0.) (M 12.00) (M 30.00) (M -18.) (M 200.00) (M 182.) (182.)
增加/减少运算 / MARK-UP/DOWN Mark up: Cost = \$2,000 Profit = 20% of selling price Selling price = ? (\$2,500) Profit = ? (\$500) Mark down: Selling price = \$2,400 Profit = 20% of cost Cost = ? (\$2,000) Profit = ? (\$400)	$2000 \div 20 \text{ MU}$ $2400 \div 20 \text{ MU}$	(2'500.00) (500.00) (2'000.00) (400.00)
溢出 / OVERFLOW $123456789 \times 78900 =$ 9740740652100 (溢出/ERROR) — $6 \div 0 = 0$ (溢出/ERROR) —	$123456789 \times 78900 =$ 9740740652100 (溢出/ERROR) — $6 \div 0 = 0$ (溢出/ERROR) —	(E 9.74074065210) (9.74074065210) (E 0.) (0.)

AS-1200

■ 在使用本产品前，请务必先仔细阅读本使用说明书。

中国语

电源

本计算器配有两种电源，太阳能及硷性电池。电池的使用时间完全取决于个别的使用情况。

(注: 不要试图自行更换电池，请到佳能维修服务中心，专业人员为您更换电池。)

■ 电磁干扰或静电放电可引起显示故障或内存中的内容丢失或改变。若出现此情况，请按 键重新开始计算。

小数点选择开关

: 设定计算结果小数点的位置 (+ 4 3 2 0 F)。



+ (加模式): 进行加减运算的时候，此机会自动把数目转化成两位小数。



F (合并小数点): 所有不超过12位的有效数字都会显示出来。

四舍五入选择开关

用作把小数化为入小数()，整数(5/4)，或舍小数()至预先设定运算结果的小数位置。

规格

电 源：太阳能电池及硷性电池 (LR44 x 1)

自动断电：约7分钟

操作温度：0 至 40度(华氏 32 至 104度)

体 积：177毫米(长) x 119毫米(宽) x 37毫米(高)

重 量：152 克

(规格如有改动恕不另行通知)

■ Before using this product, please read this manual carefully.

ENGLISH

POWER SUPPLY

This calculator comes with a dual power source, solar cell and alkaline battery. The battery life will depend on individual usage.

(Note: Do not attempt to change the battery by yourself. Have a Canon Service Center change the battery for you).

■ Electromagnetic interference or electrostatic discharge may cause the display to malfunction or the contents of the memory to be lost or altered. Should this occur, press the key and re-start your calculation from the beginning.

DECIMAL POINT SELECTOR SWITCH

: Used for designating the decimal point position (+ 4 3 2 0 F) for calculated results.



+ (Add Mode): Addition and subtraction functions are performed with an automatic 2-digit decimal. It is convenient for currency calculations.



F (Floating Decimal Point): All effective numbers up to 12 digits are displayed.

ROUNDING SWITCH

: Used for round-up [, round-off [5/4] or round-down [] to the pre-selected decimal digits in the result.

SPECIFICATION

Power Source : Solar Cell and Alkaline battery (LR44 x 1)

Automatic power-off function: Approx. 7 minutes

Usable Temperature : 0°C to 40°C (32°F to 104°F)

Dimensions : 177mm (L) x 119mm (W) x 37mm (H) / 6-31/32" (L) x 4-11/16" (W) x 1-15/32" (H)

Weight : 152 g (5.14 oz)

(Subject to change without notice)

© CANON ELECTRONIC BUSINESS MACHINES (H.K.) CO., LTD. 2012

中国印制 / Printed in China

修订日期: 2012.02

佳能电子香港有限公司
香港新界葵涌货柜码头路82-100号永得利广场第1期17楼
北京博信嘉业科技股份有限公司
北京市西城区北展北街华远企业中心D座1单元505室

备注/NOTE : 部分机身采用佳能循环再生物料制成 / Some parts are made from recycled Canon product materials