

Canon

LC-210L

EN SPECIFICATION

Power Source : Alkaline battery (LR1130 x 1)
 Automatic Power-off: approx. 8 minutes
 Dimensions: 59mm(W)x97mm(L)x10.5mm(H)
 Weight : 40g

DE TECHNISCHE DATEN

Stromversorgung: Alkalibatterie (LR1130 x 1)
 Ausschaltautomatik: Ungefähr 8 Minuten
 Abmessungen: 59mm(B)x97mm(L)x10.5mm(H)
 Gewicht: 40g

FR FICHE TECHNIQUE

Alimentation: Pile alcalines (LR1130 x 1)
 Mise hors circuit automatique: approx. 8 minutes
 Dimensions: 59 mm(W) x 97 mm(L) x 10.5 mm(H)
 Poids: 40g

ES ESPECIFICACIONES

Alimentación: Pilas alcalinas. (LR1130 x 1)
 Desconexión automática: 8 minutos
 Dimensiones: 59mm(W)x97mm(L)x10.5mm(H)
 Peso: 40g

IT SPECIFICHE

Alimentazione: Batteria alcalina (LR1130 x 1)
 Spegnimento automatico: ca. 8 minuti
 Dimensioni: 59mm(La)x97mm(P)x10.5mm(A)
 Peso: 40g

CANON ELECTRONIC BUSINESS MACHINES (H.K.) CO., LTD.

17/F., Tower One, Ever Gain Plaza,
 82-100 Container Port Road, Kwai Chung,
 New Territories, Hong Kong

CANON AUSTRALIA PTY. LTD.

Building A, The Park Estate, 5 Talavera Road,
 Macquarie Park, NSW 2113, Australia
 Tel: 13 13 83
 Website: www.canon.com.au

CANON NEW ZEALAND LTD.

Akoranga Business Park,
 28 The Warehouse Way, Northcote,
 Auckland 0627, New Zealand
 Tel: 0800 222 666
 Website: www.canon.co.nz

EZ2-4842

Made in China / Printed in China



CALCULATION EXAMPLE

Calculation	Operation	Display
		12345678
▼ MIXED		
140-35+22=127	140 35 22	(0.) (127.)
2 x 2 3 =6	2 2 3	(6.)
-7x 9 =-63	7 9	(-63.)
9+5x3.2+7 =12.76	9 5 3.2 7	(12.76)
(2+4) x 3.8 =16.2	(2 + 4) 3.8	(16.2)
▼ CONSTANT		
2+3=5	2 3	(5.)
4+3=7	4 3	(7.)
1-2=-1	1 2	(- 1.)
2-2=0	2 2	(0.)
5x3=15	5 3	(15.)
5x4=20	5 4	(20.)
6+3=2	6 3	(2.)
9+3=3	9 3	(3.)
▼ POWER, FRACTION		
3 ³ =27	3 3	(27.)
1/2 =0.5	1 2	(0.5)
▼ SQUARE ROOT		
$\sqrt{3} = 1.7320508$	3	(1.7320508)
▼ PERCENTAGE		
1,200x12%=144	1200 12	(144.)
200+(200x20%) =240	200 20	(240.)
200-(200x15%) =170	200 15	(170.)
▼ MEMORY		
3 x 4 = 12	3 4	(M 12.)
-) 6 + 0.2 = 30	6 0.2	(M 30.)
-16		(M -16.)
+) 200	200	(M 200.)
182	(Recall Memory)	(M 182.)
	(Clear Memory)	(182.)
▼ OVERFLOW		
123456x7899= 975178944 (ERROR)	123456 7899	(E 9.7517894) (0.)
6 + 0 = 0 (ERROR)	6 0	(E 0.) (0.)

5931A001[AA]



T 4960999705705